

View Online at <https://aerobasegroup.com/nsn/5305-01-603-9029>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.197 inches and 0.227 inches

Fastener Length:

Between 0.6094 inches and 0.6406 inches

Head Style:

Knurled no. 4

Head Diameter:

Between 0.307 inches and 0.317 inches

Head Height:

Between 0.2964 inches and 0.3276 inches

Point Length:

0.0937 inches

Point Diameter:

Between 0.079 inches and 0.095 inches

First Diameter From Head:

Between 0.09 inches and 0.10 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.3193 inches

Point Style:

Cone

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Point Chamfer Angle:

Between 85.0 degrees and 95.0 degrees

Product Name:

Captive panel screw

Special Features:

Has 40 straight knurled teeth per inch on head. Has 45 degree chamfers on top and base of head. Slot width of 0.047 plus or minus 0.005 inches.

Material:

Stainless steel

Material Specification:

Astma581-75 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0