

View Online at <https://aerobasegroup.com/nsn/5305-01-604-2872>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.41 inches and 0.44 inches

Fastener Length:

Between 1.285 inches and 1.315 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.3859 inches and 0.3948 inches

Head Inside Diameter:

Between 0.358 inches and 0.365 inches

Head Height:

0.057 inches

Spline Major Diameter:

Between 0.1100 inches and 0.1120 inches

Grip Diameter:

Between 0.2646 inches and 0.2651 inches

Internal Drive Style:

Torx

End Application:

F/a-18 e/f

Thread Diameter:

0.250 inches

Grip Length:

Between 0.865 inches and 0.885 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

28

Countersink Angle:

Between 99.00 degrees and 101.0 degrees

Product Name:

Bolt, 100deg reduced head, gear drive recess, inconel 71 (125ksi shear) , 0.0156 inch oversize

Special Features:

Passivate plus cetyl alcohol per mil-I-87132, type 1, grade b. See tech data for all info about finish and any other additional details

Material:

Nickel alloy

Material Specification:

Ams5662 national std/spec single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-I-87132 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-I-87132 spec.