NSN 5305-01-604-5718

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-604-5718 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.183 inches and 0.193 inches **Fastener Length:** 0.946 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.307 inches and 0.317 inches **Head Height:** Between 0.146 inches and 0.166 inches **Shoulder Diameter:** 0.1860 inches and 0.1870 inches grip **Shoulder Length:** 0.750 inches and 0.752 inches grip **Internal Drive Style:** Hexagon **End Application:** Various army items **Thread Diameter:** 0.164 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round grip **Product Name:** Bolt, shoulder **Special Features:** 0.031 x 0.176 inch diameter undercut bottom of head Color: Black Material: Steel comp 303

Material Specification:

Astm a582/a582m uns s30300 assn standard single material response

Surface Treatment:

Oxide

NSN 5305-01-604-5718

Shoulder Screw - Page 2 of 2



Mil-dtl-13294 cl 4 or mil-std-171 para 3.3.4 military standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-dtl-13294 spec.