NSN 5305-01-605-1227

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-605-1227

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.97 inches and 1.00 inches
Fastener Length:
Between 0.97 inches and 1.00 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Internal Drive Style:
Cross recess type iii
End Application:
E-3 block 404
Thread Diameter:
0.1900 inches
Thready Qty Per Inch (tpi):
32
Screw Material:
Titanium alloy uns r56400
Screw Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Bearing Surface Of Head Surface Treatment:
Aluminum
Head Surface Treatment:
Aluminum
Screw Surface Treatment:
Aluminum
Shank Surface Treatment:
Aluminum
Bearing Surface Of Head Surface Treatment Specification:
Bms10-85, type 1 mfr ref single treatment response
Head Surface Treatment Specification:
Bms10-85, type 1 mfr ref single treatment response
Screw Surface Treatment Specification:
Bms10-85, type 1 mfr ref single treatment response
Shank Surface Treatment Specification:
Rms10-85 type 1 mfr ref single treatment response

NSN 5305-01-605-1227

Machine Screw - Page 2 of 2



Special Features:
Screw, pan head, cross recess, full threaded, titanium, non-locking
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0