

View Online at <https://aerobasegroup.com/nsn/5305-01-605-2630>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.516 inches

Fastener Length:

Between 0.593 inches and 0.625 inches

Head Style:

Pan

Head Diameter:

Between 0.306 inches and 0.322 inches

Head Height:

Between 0.370 inches and 0.390 inches

Internal Drive Style:

Cross recess type iii

End Application:

5805-01-581-9251

Thread Diameter:

0.164 inches

Features Provided:

Flat washer and lock washer

Thready Qty Per Inch (tpi):

32

Product Name:

Screw, pan head, assembled washers, standard shoulder washers

Screw Material:

Stainless steel

Screw Material Specification:

Ms51957 military standard single material response

Bearing Surface Of Head Surface Treatment:

Black chemical finish and oxide

Head Surface Treatment:

Black chemical finish and oxide

Screw Surface Treatment:

Black chemical finish and oxide

Shank Surface Treatment:

Black chemical finish and oxide

Bearing Surface Of Head Surface Treatment Specification:

Mil-dtl-13924, class 4 military standard single treatment response

Head Surface Treatment Specification:

Mil-dtl-13924, class 4 military standard single treatment response

Screw Surface Treatment Specification:

Mil-dtl-13924, class 4 military standard single treatment response

Shank Surface Treatment Specification:

Mil-dtl-13924, class 4 military standard single treatment response

Special Features:

Flat washer material is corrosion resistant steel per ams-qq-763a class 302, condition b or class 304 condition a, or class 384 condition a.

Lock washer material is corrosion-resistant steel per nasm35338.

Color:

Black

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-dtl-13924 spec.