NSN 5305-01-605-5456

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-605-5456

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.403 inches
Fastener Length:
0.715 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.4421 inches and 0.5260 inches
Spline Major Diameter:
0.155 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Point Diameter:
0.240 inches
Point Style:
Flat
Internal Drive Style:
Torx
End Application:
Naval air
Thread Diameter:
0.250 inches
Grip Length:
0.312 inches
Thready Qty Per Inch (tpi):
28
Countersink Angle:
Between 129.0 degrees and 131.0 degrees
Surface Finish:
125.0 microinches grip
Product Name:
Screw, shear, 130 degrees flush head, close tolerance, nas1800 six lobe recess, 95 ksi fsu
Special Features:
Item furnished w/aluminum pigmented coating iaw nas4006 w/cetyl alcohol lubricant iaw as87132, ty iii, gr b
Material:
Titanium alloy uns r56400
Material Specification:

6al-4v iaw ams4928 or ams4967 assn standard single material response

NSN 5305-01-605-5456

Close Tolerance Screw - Page 2 of 2



Ihread	Series	Designator
Unjf		

Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

No

Fiig:

A003b0