NSN 5305-01-606-0309

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-606-0309 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.575 inches and 0.625 inches **Fastener Length:** 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Locking Feature:** Pellet **Internal Drive Style:** Cross recess type 1 **End Application:** Missle **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 55000 pounds per square inch **Screw Material:** Copper alloy 268 and copper alloy 360 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Special Features:** Altered item ms35206-218 modified with locking pellet **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-606-0309

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0