NSN 5305-01-606-4379

Thread Class:

Right-hand

Thread Direction:

2a

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-606-4379

Thread Length:
0.484 inches
Fastener Length:
Between 0.593 inches and 0.625 inches
Head Style:
Undercut pan no. 2
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.105 inches and 0.115 inches
Extended Washer Diameter:
Between 0.370 inches and 0.390 inches
Extended Washer Thickness:
Between 0.013 inches and 0.019 inches
Washer Quantity:
2
Internal Drive Style:
Cross recess type ii
End Application:
Central office, telephone, automatic
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Split helical ring
Primary Washer Outside Diameter:
Between 0.370 inches and 0.390 inches
Secondary Washer Outside Diameter:
0.296 inches
Primary Washer Style:
Flat
Primary Washer Material Thickness:
0.109 inches
Secondary Washer Material Thickness:
0.109 inches

NSN 5305-01-606-4379

Assembled Washer Screw - Page 2 of 2



Product Name:
Screw assembly
Material:
Stainless steel
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0