NSN 5305-01-608-2919

Panel Screw Assembly - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-608-2919



3aThread Direction:Right-handThread Length:Between 0.271 inches and 0.291 inchesFastener Length:Between 0.755 inches and 0.775 inchesHead Style:Modified panHead Diameter:Between 0.472 inches and 0.492 inchesHead Height:Between 0.237 inches and 0.257 inchesHearal Drive Style:HexagonEnternal Drive Style:HexagonEnternal Accommodated Thickness:0.281 inchesThread Diameter:0.2500 inchesWith Across Flats:Between 0.1875 inches and 0.1900 inchesThready Cty Per Inch (tpi):28Product Name:Screw assembly, panelMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnifSuff Life:NaFig:A003b0	Thread Class:
Right-handRight-handThread Length:Between 0.271 inches and 0.291 inchesFastener Length:Between 0.755 inches and 0.775 inchesHead Style:Modified panHead Diameter:Between 0.472 inches and 0.492 inchesHead Height:Between 0.237 inches and 0.492 inchesInternal Drive Style:HexagonEnd Application:E-3 block 404Material Accommodated Thickness:0.281 inchesThread Diameter:0.2500 inchesWidth Across Flats:Between 0.1875 inches and 0.1900 inchesThready Qty Per Inch (tpi):28Product Name:Screw assembly, panelMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnifShelf Life:N/aNaFig:NoFig:	3a
Tread Length:Between 0.271 inches and 0.291 inchesFastener Length:Between 0.755 inches and 0.775 inchesHead Style:Modified panHead Diameter:Between 0.472 inches and 0.492 inchesHead Height:Between 0.237 inches and 0.257 inchesInternal Drive Style:HexagonEnd Application:E-3 block 404Material Accommodated Thickness:0.281 inchesThread Diameter:0.2500 inchesWidth Across Flats:Between 0.1875 inches and 0.1900 inchesThready Qty Per Inch (tpi):28Product Name:Screw assembly, panelMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnifShelf Life:N/aPinilitarization:NoFig:	Thread Direction:
Tread Length:Between 0.271 inches and 0.291 inchesFastener Length:Between 0.755 inches and 0.775 inchesHead Style:Modified panHead Diameter:Between 0.472 inches and 0.492 inchesHead Height:Between 0.237 inches and 0.257 inchesInternal Drive Style:HexagonEnd Application:E-3 block 404Material Accommodated Thickness:0.281 inchesThread Diameter:0.2500 inchesWidth Across Flats:Between 0.1875 inches and 0.1900 inchesThready Qty Per Inch (tpi):28Product Name:Screw assembly, panelMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnifShelf Life:N/aPinilitarization:NoFig:	Right-hand
Between 0.271 inches and 0.291 inches Fastener Length: Between 0.755 inches and 0.775 inches Head Style: Modified pan Head Diameter: Between 0.472 inches and 0.492 inches Head Height: Between 0.237 inches and 0.257 inches Internal Drive Style: Hexagon End Application: E-3 block 404 Material Accommodated Thickness: 0.281 inches Thread Diameter: 0.2500 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Stainless steel Surface Treatment: Passivate Thread Serles Designator: Unjf Shelf Life: N/a Unit Of Measure: T Demilitarization: No Fig:	-
Between 0.755 inches and 0.775 inches Head Style: Modified pan Head Diameter: Between 0.472 inches and 0.492 inches Head Height: Between 0.237 inches and 0.257 inches Internal Drive Style: Hexagon End Application: E-3 block 404 Material Accommodated Thickness: 0.281 inches Thread Diameter: 0.2500 inches Kidth Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Screw assembly, panel Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: T Pomilitarization: No Filig:	
Between 0.755 inches and 0.775 inches Head Style: Modified pan Head Diameter: Between 0.472 inches and 0.492 inches Head Height: Between 0.237 inches and 0.257 inches Internal Drive Style: Hexagon End Application: E-3 block 404 Material Accommodated Thickness: 0.281 inches Thread Diameter: 0.2500 inches Kidth Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Screw assembly, panel Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: T Pomilitarization: No Filig:	Fastener Length:
Modified pan Head Diameter: Between 0.472 inches and 0.492 inches Head Height: Between 0.237 inches and 0.257 inches Internal Drive Style: Hexagon End Application: E-3 block 404 Material Accommodated Thickness: 0.281 inches Thread Diameter: 0.2500 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Stainless steel Stainless steel Stainless steel Stainless steel Chread Series Designator: Unif Sheif Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Modified pan Head Diameter: Between 0.472 inches and 0.492 inches Head Height: Between 0.237 inches and 0.257 inches Internal Drive Style: Hexagon End Application: E-3 block 404 Material Accommodated Thickness: 0.281 inches Thread Diameter: 0.2500 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Stainless steel Stainless steel Stainless steel Stainless steel Chread Series Designator: Unif Sheif Life: N/a Unit Of Measure: Demilitarization: No Fig:	Head Style:
Head Diameter:Between 0.472 inches and 0.492 inchesHead Height:Between 0.237 inches and 0.257 inchesInternal Drive Style:HexagonEnd Application:E-3 block 404Material Accommodated Thickness:0.281 inchesThread Diameter:0.2500 inchesWidth Across Flats:Between 0.1875 inches and 0.1900 inchesThready Qty Per Inch (tpi):28Product Name:Screw assembly, panelMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnifShelf Life:N/aUnit Of Measure:-NoFig:	-
Head Height:Between 0.237 inches and 0.257 inchesInternal Drive Style:HexagonEnd Application:E-3 block 404Material Accommodated Thickness:0.281 inchesThread Diameter:0.2500 inchesWidth Across Flats:Between 0.1875 inches and 0.1900 inchesThready Qty Per Inch (tpi):28Product Name:Screw assembly, panelMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnifShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	
Between 0.237 inches and 0.257 inches Internal Drive Style: Hexagon End Application: E-3 block 404 Material Accommodated Thickness: 0.281 inches Thread Diameter: 0.2500 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Screw assembly, panel Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.472 inches and 0.492 inches
Between 0.237 inches and 0.257 inches Internal Drive Style: Hexagon End Application: E-3 block 404 Material Accommodated Thickness: 0.281 inches Thread Diameter: 0.2500 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Screw assembly, panel Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Head Height:
HexagonEnd Application:E-3 block 404Material Accommodated Thickness:0.281 inchesThread Diameter:0.2500 inchesWidth Across Flats:Between 0.1875 inches and 0.1900 inchesThready Qty Per Inch (tpi):28Product Name:Screw assembly, panelMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:N/aInt Of Measure:Penilitarization:NoFiig:	-
HexagonEnd Application:E-3 block 404Material Accommodated Thickness:0.281 inchesThread Diameter:0.2500 inchesWidth Across Flats:Between 0.1875 inches and 0.1900 inchesThready Qty Per Inch (tpi):28Product Name:Screw assembly, panelMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:N/aInt Of Measure:Penilitarization:NoFiig:	Internal Drive Style:
End Application: E-3 block 404 Material Accommodated Thickness: 0.281 inches Thread Diameter: 0.2500 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Screw assembly, panel Material: Stainless steel Stainless steel Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No	•
E-3 block 404 Material Accommodated Thickness: 0.281 inches Thread Diameter: 0.2500 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Screw assembly, panel Material: Stainless steel Stainless steel Stainless steel Stainless steel Stainless steel Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No	·
0.281 inches Thread Diameter: 0.2500 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Screw assembly, panel Material: Stainless steel Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Thread Diameter:0.2500 inchesWidth Across Flats:Between 0.1875 inches and 0.1900 inchesThready Qty Per Inch (tpi):28Product Name:Screw assembly, panelMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Material Accommodated Thickness:
0.2500 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Screw assembly, panel Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.281 inches
Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Screw assembly, panel Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Diameter:
Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Product Name: Screw assembly, panel Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.2500 inches
Thready Qty Per Inch (tpi):28Product Name:Screw assembly, panelMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Width Across Flats:
28 Product Name: Screw assembly, panel Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.1875 inches and 0.1900 inches
Product Name: Screw assembly, panel Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thready Qty Per Inch (tpi):
Screw assembly, panel Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	28
Material:Stainless steelSurface Treatment:PassivateThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Product Name:
Stainless steel Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Screw assembly, panel
Surface Treatment: Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Passivate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Stainless steel
Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Passivate
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Unjf
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A003b0	Fiig:
	A003b0