## NSN 5305-01-608-4292

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-608-4292

View Online at https://aerobasegroup.com/nsn/5305-01-608-4292
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.594 inches
Fastener Length:
Between 1.787 inches and 1.817 inches
Head Style:
Flat countersunk
Head Diameter:
0.717 inches
Head Height:
0.167 inches
Grip Diameter:
Between 0.374 inches and 0.375 inches
Point Style:
Flat
Internal Drive Style:
High-torque
Thread Diameter:
0.375 inches
Grip Length:
Between 1.365 inches and 1.385 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
14000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Bolt, 100 degrees, flush reduced head
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

## NSN 5305-01-608-4292

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0