

View Online at <https://aerobasegroup.com/nsn/5305-01-609-0886>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.875 inches

**Fastener Length:**

Between 2.085 inches and 2.125 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.302 inches and 0.312 inches

**Head Height:**

Between 0.185 inches and 0.190 inches

**Locking Feature:**

Strip locking featurestrip head

**Internal Drive Style:**

Hexagon

**End Application:**

NSN2-35-001-3693

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.1562 inches and 0.1587 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

33.0 rockwell c and 42.0 rockwell c

**Product Name:**

Screw, cap, socket head

**Material:**

Plastic polyamide locking feature

**Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Astm a380 assn standard single treatment response fastener

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0