NSN 5305-01-610-2196

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-610-2196

view Offilite at https://aerobasegroup.com/his//5505-61-610-2150
Thread Class:
2a/2b
Thread Direction:
Right-hand
Thread Length:
0.53 inches
Fastener Length:
1.25 inches
Head Style:
Round
Head Diameter:
0.425 inches
Head Height:
0.125 inches
Internal Drive Style:
One way
End Application:
1440-01-087-9844
Material Accommodated Thickness:
1.25 inches
Thread Diameter:
0.190 inches
Features Provided:
Sleeve
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
85000 pounds per square inch
Hardness Rating:
85.0 rockwell b
Product Name:
Bolt, machine-partition sexbolt, tamperproof
Special Features:
Item is a two part assembly; sleeve style end is the same thread size as screw end with internal threads that allow for screw end and sleeve
end to fit together tightly; this item requires a special driver for removal since it is a one-way head
Material:
Stainless steel
Material Specification:
300 series cres equal to 18-8 chromium nickel alloy iaw qq-s-763 or fed-std-66 federal specification single material response
Surface Treatment:
Passivate

Qq-p-35 federal specification single treatment response or astm a380 assn standard single treatment response

Surface Treatment Specification:

NSN 5305-01-610-2196

Panel Screw Assembly - Page 2 of 2



Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0