

View Online at <https://aerobasegroup.com/nsn/5305-01-610-3439>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Fastener Length:

Between 0.622 inches and 0.633 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

60000 pounds per square inch

Product Name:

Screw, machine

Screw Material:

Steel

Bearing Surface Of Head Surface Treatment:

Cadmium

Head Surface Treatment:

Cadmium

Screw Surface Treatment:

Cadmium

Shank Surface Treatment:

Cadmium

Bearing Surface Of Head Surface Treatment Specification:

Amsqq-p-416, ty2, cl3 assn standard single treatment response

Head Surface Treatment Specification:

Amsqq-p-416, ty2, cl3 assn standard single treatment response

Screw Surface Treatment Specification:

Amsqq-p-416, ty2, cl3 assn standard single treatment response

Shank Surface Treatment Specification:

Amsqq-p-416, ty2, cl3 assn standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0