## NSN 5305-01-611-2763

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-611-2763

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.312 inches   |
| Fastener Length:   |
| 1.438 inches   |
| Head Style:  |
| Knurled no. 5  |
| Head Diameter:   |
| 0.300 inches   |
| Head Height:   |
| 0.750 inches   |
| Internal Drive Style:  |
| Hexagon  |
| End Application:   |
| Rq-4a  |
| Thread Diameter:   |
| 0.190 inches   |
| Width Across Flats:  |
| 0.156 inches   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 1600 pounds per square inch  |
| Product Name:  |
| Captive screw assembly   |
| Special Features:  |
| Use nut retainer ca28085-3-11  |
| Material:  |
| Stainless steel fastener   |
| Material Specification:  |
| Astm-a313 federal specification single material response spring      |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:                                     |
| Qq-p-416 type ii, class 2 federal standard single treatment response |
| Thread Series Designator:  |
| Unf  |
| Shelf Life:  |
| N/a  |

## NSN 5305-01-611-2763

Panel Screw Assembly - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A003b0