

View Online at <https://aerobasegroup.com/nsn/5305-01-611-4100>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.577 inches

Fastener Length:

Between 1.374 inches and 1.404 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.704 inches and 0.762 inches

Head Height:

0.160 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Internal Drive Style:

Offset cruciform (torque set)

End Application:

Kc-135 acft

Thread Diameter:

0.3750 inches

Grip Length:

Between 0.802 inches and 0.822 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Bolt, 100deg head, offset cruciform, close tolerance, 180, 000 psi

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas672 national std/spec single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas2803 through 2810 professional/industrial association standard

Specification Or Standard:

Nas2806 item and 13 length

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.