## NSN 5305-01-611-4100

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-611-4100

View Online at https://aerobasegroup.com/nsn/5305-01-611-4100
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.577 inches
Fastener Length:
Between 1.374 inches and 1.404 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.704 inches and 0.762 inches
Head Height:
0.160 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Internal Drive Style:
Offset cruciform (torque set)
End Application:
Kc-135 acft
Thread Diameter:
0.3750 inches
Grip Length:
Between 0.802 inches and 0.822 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Bolt, 100deg head, offset cruciform, close tolerance, 180, 000 psi
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military
specification 3rd material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas672 national std/spec single treatment response
Thread Series Designator:

Unjf

## NSN 5305-01-611-4100

Close Tolerance Screw - Page 2 of 2



80205-nas2803 through 2810 professional/industrial association standard

**Specification Or Standard:** 

Nas2806 item and 13 length

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.