NSN 5305-01-611-4130

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-611-4130 **Thread Direction:** Right-hand Thread Length: 22.00 millimeters Fastener Length: Between 49.50 millimeters and 50.50 millimeters **Head Style:** Fillister **Head Diameter:** Between 12.73 millimeters and 13.27 millimeters **Head Height:** Between 7.64 millimeters and 8.00 millimeters **Internal Drive Style:** Hexagon **End Application:** Mrap-buffalo a1 **Thread Diameter:** 8.0 millimeters Width Across Flats: Between 6.020 millimeters and 6.140 millimeters Min. Tensile Strength (psi): 177000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 44.0 rockwell c Minimum Yield Strength: 1100 megapascals **Thread Pitch In Millimeters:** 1.25 **Special Features:** Finish is thermal or chemical black oxide. Color: Black Material: Steel **Material Specification:** Iso 898 class 12.9 international std/spec single material response **Surface Treatment:** Oxide **Thread Series Designator:** М

Shelf Life: N/a

NSN 5305-01-611-4130

Socket Head Cap Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0