NSN 5305-01-611-7029



Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-611-7029 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.329 inches **Fastener Length:** Between 0.406 inches and 0.438 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.085 inches and 0.096 inches Washer Quantity: **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.296 inches **Secondary Washer Outside Diameter:** Between 0.307 inches and 0.317 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.040 inches **Secondary Washer Material Thickness:** Between 0.013 inches and 0.019 inches Material: Steel comp 1060 or steel comp 1561 or steel comp 1566 or steel comp 1069 or steel comp 1070 or steel comp 1071 or steel comp 1572 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp 1080 primary washer

Surface Treatment:

Cadmium and chromate

Thread Series Designator:

Unc

NSN 5305-01-611-7029

Assembled Washer Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0