

View Online at <https://aerobasegroup.com/nsn/5305-01-612-6252>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.532 inches and 0.563 inches

Fastener Length:

Between 0.532 inches and 0.563 inches

Head Style:

Flat fillister

Head Diameter:

Between 0.306 inches and 0.313 inches

Head Height:

Between 0.103 inches and 0.118 inches

Internal Drive Style:

Torque set

Thread Diameter:

0.1900 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

3180 pounds per square inch

Product Name:

Screw, machine-flat fillister head, full thread, offset cruciform

Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp e4340

Screw Material Specification:

Mil-s-5626 military specification single material response or ams6415 assn standard single material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response

Bearing Surface Of Head Surface Treatment:

Cadmium and chromate

Head Surface Treatment:

Cadmium and chromate

Screw Surface Treatment:

Cadmium and chromate

Shank Surface Treatment:

Cadmium and chromate

Bearing Surface Of Head Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Head Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Screw Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Shank Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Color:

Black

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.