## NSN 5305-01-612-8003

Machine Screw - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5305-01-612-6003
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.960 inches and 0.992 inches
Fastener Length:
Between 1.159 inches and 1.173 inches
Head Style:
Hexagon
Head Height:
Between 0.096 inches and 0.110 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Stainless steel
Screw Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response or ams 5853 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
-qq-p-35 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
63.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjc
Specification Data:
80205-nas1802 professional/industrial association standard
Shelf Life:

N/a

## NSN 5305-01-612-8003

Machine Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A500d0