

View Online at <https://aerobasegroup.com/nsn/5305-01-612-8972>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.427 inches and 0.447 inches

Fastener Length:

Between 0.615 inches and 0.635 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.307 inches and 0.312 inches

Head Height:

Between 0.092 inches and 0.095 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Width Across Flats:

0.093 inches

Features Provided:

Flat washer and lock washer

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Product Name:

Screw, assembled washer-hex socket, low profile head, crew

Special Features:

Dichromate solution is prohibited. Flat washer part number is nas620c10. Lock washer part number is ms35338-138.

Material:

Stainless steel secondary washer

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Astm a967 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0