NSN 5305-01-612-9294

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-612-9294

Thread Direction: Right-hand Thread Length: Between 9.7 millimeters and 10.3 millimeters **Fastener Length:** Between 9.7 millimeters and 10.3 millimeters **Head Style:** Flat chamfer **Head Diameter:** Between 6.80 millimeters and 7.00 millimeters **Head Height:** Between 3.88 millimeters and 4.00 millimeters **Internal Drive Style:** Hexagon **Thread Diameter:** 4.0 millimeters Width Across Flats: Between 3.020 millimeters and 3.071 millimeters Min. Tensile Strength (psi): 8720 newtons per square millimeter **Thread Pitch In Millimeters:** 0.7 **Product Name:** Screws, cap, hexagon socket head, full thread a-286, 1100mpa, metric Material: Iron alloy 660 or stainless steel **Material Specification:** Ams5731 assn standard 1st material response or ams5732 assn standard 1st material response or ams5737 assn standard 1st material response or ams5853 assn standard 2nd material response Surface Treatment: Passivate **Surface Treatment Specification:** Ams2700, method 1, class 4 assn standard single treatment response **Thread Series Designator:** Mj Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A003b0