

View Online at <https://aerobasegroup.com/nsn/5305-01-613-2740>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.345 inches and 0.405 inches

**Fastener Length:**

Between 0.345 inches and 0.405 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.282 inches and 0.294 inches

**Head Height:**

Between 0.092 inches and 0.097 inches

**Internal Drive Style:**

Cross recess type iii

**End Application:**

Improved target acquisition system (itas)

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**External Thread Tolerance Class:**

21

**Chamfer Angle:**

45.0 degrees

**Product Name:**

Screw, machine, pan head, self-sealing

**Special Features:**

O-ring material buna n and are located on the underneath side of the head

**Color:**

Black

**Material:**

Steel comp 302 or steel comp 304 or steel comp 305 or nickel alloy

**Material Specification:**

Ams 5735 assn standard single material response or astm a266 assn standard single material response or qq-s-763, stainless steel steel 302, 304, 305 or 16-13 chrome-nickel federal specification single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, class ii, black oxide, military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.