NSN 5305-01-615-0556

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-615-0556

view Offilite at https://aerobasegroup.com/nsn/33005-01-013-0330
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.577 inches and 1.592 inches
Fastener Length:
Between 1.609 inches and 1.656 inches
Head Style:
Hexagon
Head Height:
Between 0.096 inches and 0.110 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Internal Drive Style:
Cross recess type ii
Thread Diameter:
0.1640 inches
Document Type:
International organization for standardization
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Product Name:
Screw, machine
Screw Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Screw Material Specification:
Ams6382 assn standard 1st material response or ams6415 assn standard 2nd material response or ams6484 assn standard 3rd material
response or ams6325 assn standard 4th material response or ams6327 assn standard 5th material response
Screw Surface Treatment:
Cadmium
Screw Surface Treatment Specification:
Ams-qq-p-416 type ii, class 2 assn standard single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1801-08-26 professional/industrial association standard
Shelf Life:
N/a

__

Unit Of Measure:

NSN 5305-01-615-0556

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0