

View Online at <https://aerobasegroup.com/nsn/5305-01-616-2102>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.250 inches

Fastener Length:

0.410 inches

Head Style:

Hexagon extended washer

Head Height:

0.112 inches

Width Between Flats:

Between 0.306 inches and 0.312 inches

Extended Washer Diameter:

0.360 inches

Extended Washer Thickness:

Between 0.015 inches and 0.025 inches

Internal Drive Style:

W/o internal drive

End Application:

1520-01-355-8250

Material Accommodated Thickness:

Between 0.063 inches and 0.125 inches

Thread Diameter:

0.1900 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 41.0 rockwell c fastener

Product Name:

Screw, captive

Special Features:

Sleeve is made of cres 304 per ams-qq-s-763, is not rated for hardness and is cadmium plated per ams-qq-p-416 type ii, cl 2

Material:

Steel comp 8740 fastener

Material Specification:

Ams6322 or equiv national std/spec single material response fastener

Surface Treatment:

Cadmium fastener

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal standard single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0