NSN 5305-01-616-4258

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-616-4258

Right-hand Thread Length: 11.0 millimeters Fastener Length: 21.0 millimeters Head Style: Flat fillister Head Diameter: Between 12.73 millimeters and 13.27 millimeters Head Height: Between 5.32 millimeters and 5.50 millimeters Shoulder Diameter: 7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978 Thread Diameter:
11.0 millimeters Fastener Length: 21.0 millimeters Head Style: Flat fillister Head Diameter: Between 12.73 millimeters and 13.27 millimeters Head Height: Between 5.32 millimeters and 5.50 millimeters Shoulder Diameter: 7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
Fastener Length: 21.0 millimeters Head Style: Flat fillister Head Diameter: Between 12.73 millimeters and 13.27 millimeters Head Height: Between 5.32 millimeters and 5.50 millimeters Shoulder Diameter: 7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
21.0 millimeters Head Style: Flat fillister Head Diameter: Between 12.73 millimeters and 13.27 millimeters Head Height: Between 5.32 millimeters and 5.50 millimeters Shoulder Diameter: 7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
Head Style: Flat fillister Head Diameter: Between 12.73 millimeters and 13.27 millimeters Head Height: Between 5.32 millimeters and 5.50 millimeters Shoulder Diameter: 7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
Flat fillister Head Diameter: Between 12.73 millimeters and 13.27 millimeters Head Height: Between 5.32 millimeters and 5.50 millimeters Shoulder Diameter: 7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
Head Diameter: Between 12.73 millimeters and 13.27 millimeters Head Height: Between 5.32 millimeters and 5.50 millimeters Shoulder Diameter: 7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
Between 12.73 millimeters and 13.27 millimeters Head Height: Between 5.32 millimeters and 5.50 millimeters Shoulder Diameter: 7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
Head Height: Between 5.32 millimeters and 5.50 millimeters Shoulder Diameter: 7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
Between 5.32 millimeters and 5.50 millimeters Shoulder Diameter: 7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
Shoulder Diameter: 7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
7.987 millimeters and 9.951 millimeters all shoulders Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
Shoulder Length: 10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
10.0 millimeters all shoulders Internal Drive Style: Hexagon End Application: 3930-01-599-9978
Internal Drive Style: Hexagon End Application: 3930-01-599-9978
Hexagon End Application: 3930-01-599-9978
End Application: 3930-01-599-9978
3930-01-599-9978
Thread Diameter:
6.0 millimeters
Width Across Flats:
Between 4.020 millimeters and 4.095 millimeters
Thread Pitch In Millimeters:
1.0
Shoulder Shape:
Round all shoulders
Product Name:
Bolt, m8x10xm6-1 shoulder; 8mm x 10m (m6-1 thread) a2 s/s socket head shoulder screw
Special Features:
Corrosion resistant finish shall meet astm d610, grade 7 after a 100 cycles of gmw 14872
Material:
Stainless steel
Material Specification:
A2-70 stainless steel mfr ref single material response
Surface Treatment Specification:
law astm a380 assn standard single treatment response
Thread Series Designator:
M
Shelf Life:
N/a

NSN 5305-01-616-4258

Shoulder Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0