NSN 5305-01-616-5050

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-616-5050 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 0.750 inches **Head Style:** Truss **Head Diameter:** Between 0.546 inches and 0.573 inches **Head Height:** Between 0.133 inches and 0.150 inches **Spline Minor Diameter:** 0.200 inches **Spline Major Diameter:** 0.200 inches **Internal Drive Style:** Torx **End Application:** 3930-01-599-9978 **Thread Diameter:** 0.2500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 60000 pounds per square inch **Product Name:** 1/4-20x3/4 zinc truss head six-lobe asme b18.6.3 fully threaded machine screw Material: Steel **Material Specification:** Carbon steel mfr ref single material response **Surface Treatment:** Zinc **Surface Treatment Specification:** Fe/zn 3at per astm f1941 assn standard single treatment response **Thread Series Designator:**

Unc

Shelf Life:

N/a

NSN 5305-01-616-5050

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0