## NSN 5305-01-617-2339

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-617-2339

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.625 inches
Fastener Length:
1.750 inches
Head Style:
Flat fillister
Head Diameter:
Between 0.729 inches and 0.750 inches
Head Height:
Between 0.302 inches and 0.312 inches
Shoulder Diameter:
0.496 inches and 0.498 inches
Shoulder Length:
1.125 inches
Internal Drive Style:
Hexagon
End Application:
5840-01-578-4119
Thread Diameter:
0.375 inches
Width Across Flats:
0.250 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 43.0 rockwell c
Minimum Yield Strength:
120000 pounds per square inch
Shoulder Shape:
Round
Product Name:
Socket shoulder screw
Material:
Stainless steel
Thread Series Designator:
Unc

## NSN 5305-01-617-2339

Shoulder Screw - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

05047-asme b18.3-1988 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0