NSN 5305-01-618-4090

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-618-4090

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.614 inches
Fastener Length:
Between 0.875 inches and 0.915 inches
Head Style:
Flat fillister
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Internal Drive Style:
Hexagon
End Application:
1230-01-614-3412
Material Accommodated Thickness:
0.594 inches
Thread Diameter:
0.1900 inches
Width Across Flats:
Between 0.1562 inches and 0.1592 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
2240 pounds per square inch
Product Name:
Captive screw, edm flaring type magic groove, unc&unf thrd
Special Features:
Retaining ring ft1761-10p included
Material:
Iron alloy 660
Material Specification:
Ams5731 national std/spec single material response
Surface Treatment:
Passivate

Unf

Surface Treatment Specification:

Thread Series Designator:

Qq-p-35 federal specification single treatment response

NSN 5305-01-618-4090

Panel Screw Assembly - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

58794-ftd7049 manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0