Hexagon Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-619-1042

R T 2 F 2 H H B S B	hread Direction: light-hand hread Length: 0.0 millimeters astener Length: 0.0 millimeters lead Style: lexagon lead Height: etween 3.85 millimeters and 4.15 millimeters Vidth Between Flats:
Т 2 Н Н В 8 8	hread Length: 0.0 millimeters astener Length: 0.0 millimeters lead Style: lexagon lead Height: letween 3.85 millimeters and 4.15 millimeters Vidth Between Flats:
2 F 2 H H B 8 8	0.0 millimeters astener Length: 0.0 millimeters lead Style: lexagon lead Height: letween 3.85 millimeters and 4.15 millimeters Vidth Between Flats:
F 2 H H B B	astener Length: 0.0 millimeters lead Style: lexagon lead Height: letween 3.85 millimeters and 4.15 millimeters Vidth Between Flats:
2 H H B W B	0.0 millimeters lead Style: lexagon lead Height: letween 3.85 millimeters and 4.15 millimeters Vidth Between Flats:
н н в и в	lead Style: lexagon lead Height: etween 3.85 millimeters and 4.15 millimeters Vidth Between Flats:
н в и в	lexagon lead Height: etween 3.85 millimeters and 4.15 millimeters Vidth Between Flats:
н В И В	lead Height: etween 3.85 millimeters and 4.15 millimeters Vidth Between Flats:
В И В	etween 3.85 millimeters and 4.15 millimeters Vidth Between Flats:
и В	Vidth Between Flats:
В	
Е	etween 9.64 millimeters and 10.00 millimeters
	nd Application:
1	025-99-463-7551
Т	hread Diameter:
6	.0 millimeters
т	hread Pitch In Millimeters:
1	.0
N	laterial:
S	tainless steel
т	hread Series Designator:
N	1
S	helf Life:
N	l/a
U	nit Of Measure:
D	emilitarization:
N	lo
F	iig:
A	003b0