NSN 5305-01-619-2030

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-619-2030



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.595 inches and 0.625 inches Fastener Length: Between 0.965 inches and 1.005 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.729 inches and 0.750 inches **Head Height:** Between 0.302 inches and 0.312 inches **Shoulder Diameter:** 0.496 inches and 0.4983 inches first shoulder Shoulder Length: 0.370 inches and 0.380 inches first shoulder **Internal Drive Style:** Hexagon **End Application:** 3930-01-599-9978 **Thread Diameter:** 0.375 inches Width Across Flats: 0.250 inches Thready Qty Per Inch (tpi): 16 Hardness Rating: 32.0 rockwell c and 43.0 rockwell c Shoulder Shape: Round first shoulder **Special Features:** Dim equivalent to fastenal 26227 Color: Black Material: Steel **Material Specification:** Asme b18.3, alloy steel assn standard single material response **Surface Treatment:**

Black chemical finish

NSN 5305-01-619-2030

Shoulder Screw - Page 2 of 2



Surface Treatment Specification:

Asme b18.3 assn standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0