

View Online at <https://aerobasegroup.com/nsn/5305-01-620-0215>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.323 inches

**Fastener Length:**

0.760 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.338 inches and 0.381 inches

**Grip Diameter:**

Between 0.188 inches and 0.189 inches

**Single Shear Strength:**

95000 pounds per square inch

**Internal Drive Style:**

Tri-wing recess

**Thread Diameter:**

0.190 inches

**Grip Length:**

0.437 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 national std/spec single material response or ams 5732 national std/spec single material response or ams 5737 national std/spec single material response or ams 5853 national std/spec single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Nas4003 national std/spec single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

Anas 4500 through 4516/inactive/ national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0