

View Online at <https://aerobasegroup.com/nsn/5305-01-620-0215>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.323 inches

Fastener Length:

0.760 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.338 inches and 0.381 inches

Grip Diameter:

Between 0.188 inches and 0.189 inches

Single Shear Strength:

95000 pounds per square inch

Internal Drive Style:

Tri-wing recess

Thread Diameter:

0.190 inches

Grip Length:

0.437 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Iron alloy 660

Material Specification:

Ams 5731 national std/spec single material response or ams 5732 national std/spec single material response or ams 5737 national std/spec single material response or ams 5853 national std/spec single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Nas4003 national std/spec single treatment response

Thread Series Designator:

Unjf

Specification Data:

Anas 4500 through 4516/inactive/ national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0