## NSN 5305-01-620-5386

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-620-5386 **Thread Direction:** Right-hand Thread Length: Between 0.240 inches and 0.260 inches **Fastener Length:** 1.00 inches **Head Style:** Flat fillister **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches First Diameter From Head: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.75 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity: Product Name:** Captive socket head cap screws Material: Steel property class 18.8 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072-c, type 1 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A003b0

## NSN 5305-01-620-5386

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-14072-c spec.