## NSN 5305-01-621-2339

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-621-2339

| Thread Class:  |
|--|
| За   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.776 inches   |
| Fastener Length:   |
| 0.714 inches   |
| Head Style:  |
| Undercut pan no. 2   |
| Head Diameter:   |
| Between 0.352 inches and 0.373 inches  |
| Head Height:   |
| 0.127 inches   |
| Spline Major Diameter:   |
| 0.155 inches   |
| Grip Diameter:   |
| Between 0.1890 inches and 0.1895 inches  |
| Internal Drive Style:  |
| D24 torx   |
| Thread Diameter:   |
| 0.190 inches   |
| Grip Length:   |
| 0.500 inches   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 3180 pounds per square inch  |
| Product Name:  |
| Screw, shear, pan head, close tolerence  |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams 5731 federal specification 1st material response or ams 5732 federal specification 2nd material response or ams 5853 federal |
| specification 4th material response  |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:   |
| Ms-qq-p-4416, type 2, class 2 federal specification single treatment response  |
| Thread Series Designator:  |
| Unjf   |
| Shelf Life:  |
| N/a  |
|  |

## NSN 5305-01-621-2339

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

