

View Online at <https://aerobasegroup.com/nsn/5305-01-621-2356>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.026 inches

**Fastener Length:**

0.714 inches

**Head Style:**

Undercut pan no. 2

**Head Diameter:**

Between 0.352 inches and 0.373 inches

**Head Height:**

0.127 inches

**Spline Major Diameter:**

0.155 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Internal Drive Style:**

Torx

**Thread Diameter:**

0.190 inches

**Grip Length:**

0.750 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

3180 pounds per square inch

**Product Name:**

Screw, shear, pan head, close tolerance

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 federal specification 1st material response or ams 5732 federal specification 2nd material response or ams 5853 federal specification 4th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ms-qq-p-4416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0