

View Online at <https://aerobasegroup.com/nsn/5305-01-622-0182>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.438 inches

Fastener Length:

1.719 inches

Head Style:

Round extended washer

Head Diameter:

0.312 inches

Head Height:

Between 0.082 inches and 0.092 inches

Extended Washer Diameter:

0.375 inches

Extended Washer Thickness:

Between 0.023 inches and 0.028 inches

Spline Minor Diameter:

0.155 inches

Spline Major Diameter:

0.145 inches

Grip Diameter:

Between 0.1625 inches and 0.1635 inches

Point Diameter:

0.160 inches

Single Shear Strength:

95000 pounds per square inch

Point Style:

Flat

Internal Drive Style:

Torx

End Application:

Cowling instl; ah-1 4 bladed rotor head upgrade

Thread Diameter:

0.164 inches

Grip Length:

1.281 inches

Features Provided:

Washer

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2225 pounds per square inch

Product Name:

Screw, washer head, close tolerance, long thread, 95 kdi fsu

Material:

Stainless steel

Material Specification:

286 iaw ams5731 or ams5732 or ams5737 or ams5859 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 assn standard single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0