NSN 5305-01-622-4861

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-622-4861 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.338 inches **Fastener Length:** Between 0.583 inches and 0.601 inches **Head Style:** Flat countersunk **Head Diameter:** 0.2083 inches **Grip Diameter:** 0.1625 inches **Internal Drive Style:** Offset cruciform (torque set) **End Application:** B-1 **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, flat, 100 deg. Reduced head, 108 ksi shear Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response and mil-s-5000 military specification 2nd material response and mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type s, class 2 federal specification single treatment response **Thread Series Designator:** Unjc

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-622-4861

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.