NSN 5305-01-622-6163



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-622-6163 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.280 inches **Fastener Length:** Between 0.8325 inches and 0.8525 inches **Head Style:** Countersunk cylindrical convex **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Head Major Diameter:** Between 0.2532 inches and 0.2605 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.1640 inches **Grip Length:** 0.5625 inches **Features Provided:** Cetyl alcohol lubricant Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 100.0 degrees **Special Features:** Item has a hex hole in the end of it that is 0.0791 - 0.0806 inches across the flats and 0.080 inches deep. Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Bms10-85, type 1, class a mfr ref single treatment response **Thread Series Designator:**

Unjc

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-622-6163

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0