

View Online at <https://aerobasegroup.com/nsn/5305-01-622-9665>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.276 inches

**Fastener Length:**

Between 0.823 inches and 0.853 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.309 inches and 0.331 inches

**Head Height:**

Between 0.088 inches and 0.102 inches

**Grip Diameter:**

Between 0.1625 inches and 0.1635 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.1640 inches

**Grip Length:**

Between 0.552 inches and 0.572 inches

**Thready Qty Per Inch (tpi):**

32

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Screw, machine, pan head, modified, close tolerance, short thread, offset cruciform

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731, 5732, 5737 or 5853 national std/spec single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Clean/passivate iaw qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas1141 through 1148 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0