

View Online at <https://aerobasegroup.com/nsn/5305-01-623-3963>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.338 inches

Fastener Length:

Between 0.761 inches and 0.791 inches

Head Style:

Flat countersunk

Head Diameter:

0.2083 inches

Grip Diameter:

Between 0.1625 inches and 0.1635 inches

Internal Drive Style:

Offset cruciform (torque set)

End Application:

B-1

Thread Diameter:

0.1640 inches

Grip Length:

Between 0.428 inches and 0.448 inches

Thread Qty Per Inch (tpi):

32

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.