## NSN 5305-01-623-4040

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-623-4040

Thread Class:         3a         Thread Direction:         Right-hand         Thread Length:         0.276 inches         Fastener Length:         0.651 inches         Head Style:         Undercut pan no. 2         Head Diameter:         Between 0.357 inches and 0.373 inches         Head Height:         0.127 inches         Spline Major Diameter:         0.155 inches         Grip Diameter:         0.158 inches         Brine Major Diameter:         0.159 inches         Grip Diameter:         0.159 inches         Brtread Diameter:         0.159 inches         Grip Length:         0.159 inches         Brtread Diameter:         0.159 inches         Brtread Diameter:         0.150 inches         Grip Length:         0.190 inches         Grip Length:         0.375 inches         Thready Quy Per Inch (tpi):         32         Min. Tensile Strength (psi):         3180 pounds per square inch         Product Name:         Stainless steel         Surface Treatment:
Thread Direction: Right-hand Thread Length: 0.276 inches Fastener Length: 0.651 inches Head Style: Undercut pan no. 2 Head Diameter: Between 0.357 inches and 0.373 inches Head Height: 0.127 inches Spline Major Diameter: 0.155 inches Grip Diameter: 0.155 inches Grip Diameter: 0.158 inches Internal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.375 inches Grip Length: 0.375 inches Grip Length: 0.375 inches Chread Nameter: 0.190 inches Chread Nameter: 0.190 inches Grip Length: 0.375 inches Chread Nameter: 0.375 inches C
Right-handRight-handThread Length:0.276 inchesFastener Length:0.651 inchesHead Style:Undercut pan no. 2Head Diameter:Between 0.357 inches and 0.373 inchesHead Height:0.127 inchesSpline Major Diameter:0.127 inchesSpline Major Diameter:0.155 inchesGrip Diameter:0.189 inchesInternal Drive Style:TorxThread Diameter:0.190 inchesGrip Length:0.375 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):3180 pounds per square inchProduct Name:Screw, shear, pan head, close tolerance, six lobe recessMaterial:Stainless steelSurface Treatment:Cadmium
Thread Length: 0.276 inches Fastener Length: 0.651 inches Head Style: Undercut pan no. 2 Head Diameter: Between 0.357 inches and 0.373 inches Head Height: 0.127 inches O.127 inches Spline Major Diameter: 0.127 inches Spline Major Diameter: 0.155 inches Grip Diameter: 0.158 inches Grip Diameter: 0.189 inches Internal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Stainless steel Stainless steel Surface Treatment: Cadmium
0.276 inches Fastener Length: 0.651 inches Head Style: Undercut pan no. 2 Head Diameter: Between 0.357 inches and 0.373 inches Head Height: 0.127 inches Spline Major Diameter: 0.127 inches Spline Major Diameter: 0.127 inches Grip Diameter: 0.155 inches Grip Diameter: 0.189 inches Herenal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Stainless steel Stainless steel Stainless steel Stainless steel Stainless steel Stainless steel Cadmium
Fastener Length:0.651 inchesHead Style:Undercut pan no. 2Head Diameter:Between 0.357 inches and 0.373 inchesHead Height:0.127 inchesSpline Major Diameter:0.127 inchesGrip Diameter:0.155 inchesGrip Diameter:0.189 inchesInternal Drive Style:TorxThread Diameter:0.190 inchesGrip Length:0.375 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):3180 pounds per square inchProduct Name:Screw, shear, pan head, close tolerance, six lobe recessMaterial:Stainless steelSurface Treatment:Cadmium
0.651 inchesHead Style:Undercut pan no. 2Head Diameter:Between 0.357 inches and 0.373 inchesHead Height:0.127 inchesSpline Major Diameter:0.125 inchesGrip Diameter:0.155 inchesGrip Diameter:0.189 inchesInternal Drive Style:TorxThread Diameter:0.190 inchesGrip Length:0.375 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):3180 pounds per square inchProduct Name:Screw, shear, pan head, close tolerance, six lobe recessMaterial:Stainless steelSurface Treatment:Cadmium
Head Style: Undercut pan no. 2 Head Diameter: Between 0.357 inches and 0.373 inches Head Height: 0.127 inches Spline Major Diameter: 0.127 inches Spline Major Diameter: 0.155 inches Grip Diameter: 0.189 inches Internal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Stainless steel Surface Treatment: Cadmium
Undercut pan no. 2 Head Diameter: Between 0.357 inches and 0.373 inches Head Height: 0.127 inches Spline Major Diameter: 0.125 inches Grip Diameter: 0.155 inches Grip Diameter: 0.189 inches Internal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
Head Diameter:Between 0.357 inches and 0.373 inchesHead Height:0.127 inchesSpline Major Diameter:0.155 inchesGrip Diameter:0.158 inchesHernal Drive Style:TorxThread Diameter:0.190 inchesGrip Length:0.375 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):3180 pounds per square inchProduct Name:Screw, shear, pan head, close tolerance, six lobe recessMaterial:Stainless steelSurface Treatment:Cadmium
Between 0.357 inches and 0.373 inches Head Height: 0.127 inches Spline Major Diameter: 0.155 inches Grip Diameter: 0.189 inches Internal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
Head Height:0.127 inchesSpline Major Diameter:0.155 inchesGrip Diameter:0.189 inchesInternal Drive Style:TorxThread Diameter:0.190 inchesGrip Length:0.375 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):3180 pounds per square inchProduct Name:Screw, shear, pan head, close tolerance, six lobe recessMaterial:Stainless steelSurface Treatment:Cadmium
0.127 inches Spline Major Diameter: 0.155 inches Grip Diameter: 0.189 inches Internal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
Spline Major Diameter: 0.155 inches Grip Diameter: 0.189 inches Internal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
0.155 inches Grip Diameter: 0.189 inches Internal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
Grip Diameter: 0.189 inches Internal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
0.189 inches Internal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Stainless steel Surface Treatment: Cadmium
Internal Drive Style: Torx Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
Torx Thread Diameter: 0.190 inches Orip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
Thread Diameter: 0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Stainless steel Surface Treatment: Cadmium
0.190 inches Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
Grip Length: 0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Stainless steel Cadmium
0.375 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Stainless steel Surface Treatment: Cadmium
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Stainless steel Surface Treatment: Cadmium
32 Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
Min. Tensile Strength (psi): 3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
3180 pounds per square inch Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
Product Name: Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
Screw, shear, pan head, close tolerance, six lobe recess Material: Stainless steel Surface Treatment: Cadmium
Material: Stainless steel Surface Treatment: Cadmium
Stainless steel Surface Treatment: Cadmium
Surface Treatment: Cadmium
Cadmium
Surface Treatment Specification:
Ms-qq-p-4416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5305-01-623-4040

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

