NSN 5305-01-624-3072

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-624-3072

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.323 inches
Fastener Length:
Between 0.870 inches and 0.900 inches
Head Style:
Pan
Head Diameter:
Between 0.1845 inches and 0.1859 inches
Head Height:
Between 0.122 inches and 0.133 inches
Grip Diameter:
Between 0.357 inches and 0.373 inches
Shank Unthreaded Hole Diameter:
0.070 inches and 0.075 inches all holes
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.1900 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
32
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.721 inches all holes
Product Name:
Bolt, pan head, close tolerance, short thread, cruciform recess, a286 cres, self-locking and nonlocking
Material:
Iron alloy 660
Material Specification:
Ams5731, ams5732, ams5737 or ams5853 national std/spec single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type ii, class 2 federal specification single treatment response
Thread Series Designator:
Unif
Specification Data:
•
80205-nas7800 through 7806 professional/industrial association standard

NSN 5305-01-624-3072

Close Tolerance Screw - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0