

View Online at <https://aerobasegroup.com/nsn/5305-01-625-0774>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.783 inches and 0.813 inches

Fastener Length:

Between 0.783 inches and 0.813 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.1120 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

35000 pounds per square inch

Product Name:

Screw, machine, pan head

Screw Material:

Stainless steel

Bearing Surface Of Head Surface Treatment:

Passivate

Head Surface Treatment:

Passivate

Screw Surface Treatment:

Passivate

Shank Surface Treatment:

Passivate

Bearing Surface Of Head Surface Treatment Specification:

Mil-dtl-14072, finish e300 military specification single treatment response

Head Surface Treatment Specification:

Mil-dtl-14072, finish e300 military specification single treatment response

Screw Surface Treatment Specification:

Mil-dtl-14072, finish e300 military specification single treatment response

Shank Surface Treatment Specification:

Mil-dtl-14072, finish e300 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-dtl-14072 spec.