

View Online at <https://aerobasegroup.com/nsn/5305-01-626-8201>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.406 inches

Fastener Length:

0.968 inches

Head Style:

Oval countersunk undercut

Head Diameter:

Between 0.2966 inches and 0.3016 inches

Head Height:

Between 0.056 inches and 0.060 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.070 inches and 0.075 inches

Internal Drive Style:

High-torque

End Application:

F-15sa

Thread Diameter:

0.1900 inches

Grip Length:

0.562 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.847 inches and 0.857 inches

Product Name:

Screw-close tolerance, 100 degrees countersunk, reduced head, hi-torque

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0