

View Online at <https://aerobasegroup.com/nsn/5305-01-626-8201>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.406 inches

**Fastener Length:**

0.968 inches

**Head Style:**

Oval countersunk undercut

**Head Diameter:**

Between 0.2966 inches and 0.3016 inches

**Head Height:**

Between 0.056 inches and 0.060 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches and 0.075 inches

**Internal Drive Style:**

High-torque

**End Application:**

F-15sa

**Thread Diameter:**

0.1900 inches

**Grip Length:**

0.562 inches

**Features Provided:**

Cetyl alcohol lubricant

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.847 inches and 0.857 inches

**Product Name:**

Screw-close tolerance, 100 degrees countersunk, reduced head, hi-torque

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0