

View Online at <https://aerobasegroup.com/nsn/5305-01-626-8202>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.641 inches

Fastener Length:

Between 1.438 inches and 1.468 inches

Head Style:

Flat countersunk

Head Diameter:

0.510 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches and 0.111 inches

Internal Drive Style:

High-torque

End Application:

F-15sa

Thread Diameter:

0.3750 inches

Grip Length:

0.812 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

24

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.338 inches and 1.343 inches

Product Name:

Screw-close tolerance, 100 degrees c-sunk, reduced head, hi-torque

Material:

Nickel alloy 718

Material Specification:

Ams 5662 federal specification single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-dtl-83488, type ii, class 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-dtl-83488 spec.