

View Online at <https://aerobasegroup.com/nsn/5305-01-626-8203>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.531 inches

**Fastener Length:**

1.719 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.429 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches and 0.081 inches

**Internal Drive Style:**

Recessed type i

**End Application:**

F-15sa

**Thread Diameter:**

0.3125 inches

**Grip Length:**

1.188 inches

**Features Provided:**

Cetyl alcohol lubricant

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.595 inches and 1.605 inches

**Product Name:**

Screw-close tolerance, 100 degrees c'sunk, reduced head, high torque

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 federal specification single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Mil-dtl-83488, type ii, class 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-dtl-83488 spec.