

View Online at <https://aerobasegroup.com/nsn/5305-01-626-8203>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.531 inches

Fastener Length:

1.719 inches

Head Style:

Flat countersunk

Head Diameter:

0.429 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Unthreaded Hole Diameter:

0.076 inches and 0.081 inches

Internal Drive Style:

Recessed type i

End Application:

F-15sa

Thread Diameter:

0.3125 inches

Grip Length:

1.188 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

24

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.595 inches and 1.605 inches

Product Name:

Screw-close tolerance, 100 degrees c'sunk, reduced head, high torque

Material:

Nickel alloy 718

Material Specification:

Ams 5662 federal specification single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-dtl-83488, type ii, class 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-dtl-83488 spec.