

View Online at <https://aerobasegroup.com/nsn/5305-01-626-8204>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.312 inches

**Fastener Length:**

0.750 inches

**Head Style:**

Oval countersunk undercut

**Head Diameter:**

Between 0.2966 inches and 0.3016 inches

**Head Height:**

Between 0.056 inches and 0.060 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches and 0.075 inches

**Internal Drive Style:**

High-torque

**End Application:**

F-15sa

**Thread Diameter:**

0.1900 inches

**Grip Length:**

0.438 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.629 inches and 0.639 inches

**Product Name:**

Screw, machine, 100 degrees c'sunk, hi-torque, reduced head

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 federal specification single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Mil-c-83488, type ii, class 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.